



TFC Coaxial Cable Product Information Sheet

Type: T660-FE (AA) BLACK

Series 6 Coaxial Cable
 Copper Clad Steel Conductor
 Foamed Polyethylene Dielectric
 Bonded APA Laminate Shield
 60% Aluminum Braid
 Underground Floodant
 Black Polyethylene Jacket
 Animal Aversive



Cable Ordering Information

Part Number	Description	NEC / CSA Listing
006S60E84BK0610000R1	T660-FE (AA) BLACK	none

Characteristics

Material	Detail	inches	mm
Inner Conductor	Copper Clad Steel	0.0403	1.02
Dielectric	Foamed Polyethylene	0.180	4.57
1 st Outer Conductor	Sealed APA Tape	0.188	4.78
2 nd Outer Conductor	60% Aluminum Braid	0.212	5.38
3 rd Outer Conductor	---	---	---
4 th Outer Conductor	---	---	---
Floodant	Underground	---	---
Jacket	Polyethylene, Black, AA	0.273	6.93
Twisted Pairs	---	---	---
Messenger	---	---	---

Mechanical Specifications

Minimum Bend Radius, in. (mm)		1.0	(25.40)
Product Weight	(less reel)	24 lbs /kft	

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t660-fe (aa) black_1ghz15.docx
 Revision: 1.6.2015
 Page: 1 of 2

Times Fiber Communications, Inc.
 358 Hall Avenue
 Wallingford, CT 06492
 Toll Free +1-800-677-2288
 Toll +1-434-432-1800
 Fax +1-434-432-1821
www.timesfiber.com

uncontrolled copy

All Rights Reserved,
 Specifications subject to change without notice

