




TFC Coaxial Cable Product Information Sheet

Type: T6TQP77-FE (AA) BLACK

Series 6 Coaxial Cable
 Copper Clad Steel Conductor
 Foamed Polyethylene Dielectric
 Bonded APA Laminate Shield
 77% Aluminum Braid
 Underground Floodant
 APA Laminate Shield (QuickPrep)
 Black Polyethylene Jacket
 Animal Aversive



Cable Ordering Information

Part Number	Description	NEC / CSA Listing
006E77E84BK0610000R1	T6TQP77-FE (AA) BLACK	none

Characteristics

Material	Detail	inches	mm
Inner Conductor	Copper Clad Steel	0.0403	1.02
Dielectric	Foamed Polyethylene	0.180	4.57
1 st Outer Conductor	Sealed APA Tape	0.188	4.78
2 nd Outer Conductor	77% Aluminum Braid	0.212	5.38
3 rd Outer Conductor	APA Tape (QuickPrep)	0.216	5.49
4 th Outer Conductor	---	---	---
Floodant	Underground	---	---
Jacket	Polyethylene, Black AA	0.278	7.06
Twisted Pairs	---	---	---
Messenger	---	---	---

Mechanical Specifications

Minimum Bend Radius, in. (mm)		1.0	(25.40)
Product Weight	(less reel)	25 lbs /kft	

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t6tqp77-fe (aa) black_1ghz15.docx
 Revision: 1.8.2015
 Page: 1 of 2

Times Fiber Communications, Inc.
 358 Hall Avenue
 Wallingford, CT 06492
 Toll Free +1-800-677-2288
 Toll +1-434-432-1800
 Fax +1-434-432-1821
www.timesfiber.com

uncontrolled copy

All Rights Reserved,
Specifications subject to change without notice



TFC Coaxial Cable Product Information Sheet

Type: T6TQP77-FE (AA) BLACK

Electrical Specifications		
Impedance, Ω	75 \pm 3	
Velocity of Propagation, %	85	
Capacitance, Nominal	16.2 pF/ft	53.2 pF/m
DC Resistance	Ω / kft	Ω / km
Inner Conductor	31.0	102
Outer Conductor	5.70	19
Loop	36.7	120

Notes:

Attenuation, Maximum @ 68 °F (20 °C)		
Frequency, MHz	dB / 100 ft	dB / 100 m
5	0.58	1.90
55	1.60	5.25
211	3.05	10.01
250	3.30	10.83
270	3.37	11.06
300	3.55	11.65
330	3.74	12.27
350	3.85	12.63
400	4.15	13.62
450	4.40	14.44
500	4.66	15.29
550	4.90	16.08
600	5.10	16.73
750	5.65	18.54
870	6.11	20.05
1000	6.55	21.49

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t6tqp77-fe (aa) black_1ghz15.docx
 Revision: 1.8.2015
 Page: 2 of 2

Times Fiber Communications, Inc.
 358 Hall Avenue
 Wallingford, CT 06492
 Toll Free +1-800-677-2288
 Toll +1-434-432-1800
 Fax +1-434-432-1821
www.timesfiber.com

uncontrolled copy
 All Rights Reserved,
 Specifications subject to change without notice