

# T10 TeleDrop Cable Series

TIMES FIBER COMMUNICATIONS, INC.®

1-800-677-2288



Standard Offerings	Series 59	Series 6	Series 7	Series 11
53% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 22 AWG	623AA T5953-LTEB-2X22	—	—	623UA T1153-LTEB-2X22
53% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 22 AWG, Shielded	623AB T5953-LTEB-2X22S	—	—	623UB T1153-LTEB-2X22S
53% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 24 AWG	623BA T5953-LTEB-2X24	—	—	623VA T1153-LTEB-2X24
53% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 24 AWG, Shielded	623BB T5953-LTEB-2X24S	—	—	623VB T1153-LTEB-2X24S
53% Braid Coverage, lifeTime™, PVC Jacket, Black, 2 pair 24 AWG	623B3 T5953-LTVB-2X24	—	—	—
53% Braid Coverage, lifeTime™, PVC Jacket, Color, 2 pair 24 AWG	623BL T5953-LTVC-2X24	—	—	—
53% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 26 AWG	623CA T5953-LTEB-2X26	—	—	623WA T1153-LTEB-2X26
53% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 26 AWG, Shielded	623CB T5953-LTEB-2X26S	—	—	623WB T1153-LTEB-2X26S
60% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 22 AWG	—	623GA T660-LTEB-2X22	623NA T760-LTEB-2X22	—
60% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 22 AWG, Shielded	—	623GB T660-LTEB-2X22S	623NB T760-LTEB-2X22S	—
60% Braid Coverage, lifeTime™, Polyethylene Jacket, Color, 2 pair 22 AWG	—	623GM T660-LTEC-2X22	—	—
60% Braid Coverage, lifeTime™, Polyethylene Jacket, Color, 2 pair 22 AWG, Shielded	—	623GH T660-LTEC-2X22S	—	—
60% Braid Coverage, lifeTime™, PVC Jacket, Color, 2 pair 22 AWG, Shielded	—	623GE T660-LTVC-2X22S	—	—
60% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 24 AWG	—	623HA T660-LTEB-2X24	623PA T760-LTEB-2X24	—
60% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 24 AWG, Shielded	—	623HB T660-LTEB-2X24S	623PB T760-LTEB-2X24S	—
60% Braid Coverage, lifeTime™, PVC Jacket, Black Flame Retardant, 2 pair 24 AWG	—	623HD T660-LTVBFR-2X24	—	—
60% Braid Coverage, lifeTime™, PVC Jacket, Color Flame Retardant, 2 pair 24 AWG	—	623HF T660-LTVCFR-2X24	—	—
60% Braid Coverage, lifeTime™, PVC Jacket, Color, 2 pair 24 AWG	—	623HL T660-LTVC-2X24	—	—
60% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 26 AWG	—	623JA T660-LTEB-2X26	623QA T760-LTEB-2X26	—
60% Braid Coverage, lifeTime™, Polyethylene Jacket, Black, 2 pair 26 AWG, Shielded	—	623JB T660-LTEB-2X26S	—	—
60% Braid Coverage, lifeTime™, Polyethylene Jacket, Color, 2 pair 26 AWG	—	623JM T660-LTEC-2X26	—	—
60% Braid Coverage, lifeTime™, PVC Jacket, Black, 2 pair 26 AWG	—	623J3 T660-LTVB-2X26	—	—
60% Braid Coverage, lifeTime™, PVC Jacket, Color, 2 pair 26 AWG	—	623JL T660-LTVC-2X26	—	—

## TWISTED PAIRS ELECTRICAL PROPERTIES (per ASTM D-4566)

Impedance (nominal @ 1MHz)	100 Ohms
Mutual Capacitance (nominal)	90pf/km
Resistance Unbalance (maximum)	5%
Near End Crosstalk @ 772 kHz	-44dB min.
Far End Crosstalk @ 150 kHz	-63dB/305m min.

### Features Standard TFC T10 Drop Cables Combined with:

- Standard color-coded twisted pairs - 22 AWG , 24 AWG, 26 AWG
- One (1) through six (6) pairs available
- Overall, flooded coaxial and paired core filled with moisture blocking corrosion protectant, TFC's lifeTime™
- Optional shield of laminated Aluminum/Poly/Aluminum tape
- Outer jacket of black weather resistant polyethylene flame retardant PVC, or PE

